

## ROPE 3 & 8 Strand

Manila Rope  
 Sisal Rope  
 Polypropylene Rope  
 Silver (PE) Rope  
 PE Mono Rope  
 Polydacron Rope  
 Polyester Rope  
 Nylon Rope  
 Square (8 Strand)  
 Hardy Hemp  
 Dyneema  
 Cotton Rope  
 Mini Coils  
 Anchor Ropes

## CORDS Braids & Plaits

Absailing Rope  
 Brickets Line  
 Cod End Line  
 Dinghy Braid  
 Double Braid  
 Flag Cord  
 Lead Core Line  
 Luff Cord/Leech Line  
 Motor Starter Cord  
 Polyester Cord Pltd  
 Pre-stretch 8 Plt  
 Sash Cord, Braided  
 Shock Cord  
 Ski Rope  
 Spectra Cord  
 Vectra Cord  
 VB Cord  
 Webbing

## TWINES

Baler Twine  
 Binder Twine  
 Butchers Twine  
 Garden Twine  
 Jute Market Garden  
 Jute Sewing Twine  
 Lashing  
 Plumbers Hemp  
 Sailmakers Twine  
 Shop Twine  
 Tarred Marline  
 Ticketing Twine  
 Tomato Twine  
 Whipping Twine

## NETS/LADDERS

Rope Nets  
 Tie Down Nets  
 Rope Ladders

## OTHER ITEMS

Clothes Line  
 Barbed Wire Cutters  
 Heat Cutters  
 Rope Measurer

## DOOR MATS

Coir Door Mats  
 Wire Brush Mats  
 Coir Mat Logos

## NYLON ROPE (3 Strand)

**Characteristics:** Soft on hands. High Strength.  
 Knots well. Medium Lay. Shock absorbent.  
 Resistant to rot and mildew. Sinking rope.

**Applications:** Tie Down, Camping, Swings/  
 Kids outdoor play, Boating, Barrier Rope.

Available on request in other colours, sizes and  
 8 strand construction.



Code	Size	Length	Lay	Colour	Weight	*B/S
<b>Spools</b>						
NY06S250	6mm	250m	Medium	White	5.7kg	0.75 t
NY08S125	8mm	125m	Medium	White	5.1kg	1.35 t
NY10S125	10mm	125m	Medium	White	7.9kg	2.08 t
NY12S080	12mm	80m	Medium	White	7.2kg	3.00 t
NY12S125	12mm	125m	Medium	White	11.3kg	3.00 t
NY14S125	14mm	125m	Medium	White	15.5kg	4.10 t
NY16S050	16mm	50m	Medium	White	8.0kg	5.30 t
<b>Coils</b>						
NY04C250	4mm	250m	Medium	White	2.7kg	0.32 t
NY06C250	6mm	250m	Medium	White	5.7kg	0.75 t
NY08C250	8mm	250m	Medium	White	10.2kg	1.35 t
NY10C250	10mm	250m	Medium	White	15.7kg	2.08 t
NY12C250	12mm	250m	Medium	White	22.6kg	3.00 t
NY14C125	14mm	125m	Medium	White	15.5kg	4.10 t
NY14C250	14mm	250m	Medium	White	31.0kg	4.10 t
NY16C125	16mm	125m	Soft	White	20.0kg	5.30 t
NY16C250	16mm	250m	Medium	White	40.1kg	5.30 t
NY18C125	18mm	125m	Medium	White	25.4kg	6.70 t
NY18C250	18mm	250m	Medium	White	50.8kg	6.70 t
NY20C125	20mm	125m	Medium	White	31.1kg	8.30 t
NY20C250	20mm	250m	Medium	White	62.2kg	8.30 t
NY24C125	24mm	125m	Medium	White	45.1kg	12.03 t
NY24C250	24mm	250m	Medium	White	90.1kg	12.03 t
NY28C250	28mm	250m	Medium	White	123.0kg	15.80 t
NY32C125	32mm	125m	Medium	White	80.0kg	19.98 t
NY32C250	32mm	250m	Medium	White	160.0kg	19.98 t

\*B/S- Breaking strengths quoted are based either on the Australian rope standards or in the absence of standards the manufacturers stated breaking strength. They are approximate and for comparison purposes only. **The breaking strength should never be considered as the safe working load of the rope.**