

## ROPE 3 & 8 Strand

Manila Rope  
 Sisal Rope  
 Polypropylene Rope  
 Silver (PE) Rope  
 PE Mono Rope  
 Polydacron Rope  
 Polyester Rope  
 Nylon Rope  
 Square (8 Strand)  
 Hardy Hemp  
 Dyneema  
 Cotton Rope  
 Mini Coils  
 Anchor Ropes

## CORDS Braids & Plaits

Abseiling Rope  
 Brickies Line  
 Cod End Line  
 Dinghy Braid  
 Double Braid  
 Flag Cord  
 Lead Core Line  
 Luff Cord/Leech Line  
 Motor Starter Cord  
 Polyester Cord Pltd  
 Pre-stretch 8 Plt  
 Sash Cord, Braided  
 Shock Cord  
 Ski Rope  
 Spectra Cord  
 Vectra Cord  
 VB Cord  
 Webbing

## TWINES

Baler Twine  
 Binder Twine  
 Butchers Twine  
 Garden Twine  
 Jute Market Garden  
 Jute Sewing Twine  
 Lashing  
 Plumbers Hemp  
 Sailmakers Twine  
 Shop Twine  
 Tarred Marline  
 Ticketing Twine  
 Tomato Twine  
 Whipping Twine

## NETS/LADDERS

Rope Nets  
 Tie Down Nets  
 Rope Ladders

## OTHER ITEMS

Clothes Line  
 Barbed Wire Cutters  
 Heat Cutters  
 Rope Measurer

## DOOR MATS

Coir Door Mats  
 Wire Brush Mats  
 Coir Mat Logos

## 8 PLAIT PRE-STRETCHED CORD

**Characteristics:** Continuous filament polyester core and a polyester cover.

Pre-stretched, low twist, strong core, low extension at high loads, hardwearing and flexible.

**Uses:** Halyards, sheets, uphauled/downhauled/outhauls, control lines, guylines, general purpose.

**Colours:** White, Red, Blue, Lime with flecks.



Code	Size	Length	Colour	Weight	*B/S
PS04X200W	4mm	200m	White	2.6kg	0.33 t
PS04X200R	4mm	200m	Red	2.6kg	0.33 t
PS04X200BU	4mm	200m	Blue	2.6kg	0.33 t
PS04X200L	4mm	200m	Lime	2.6kg	0.33 t
PS05X200W	5mm	200m	White	4.2kg	0.53 t
PS05X200R	5mm	200m	Red	4.2kg	0.53 t
PS05X200BU	5mm	200m	Blue	4.2kg	0.53 t
PS05X100BU	5mm	100m	Blue	2.1kg	0.53 t
PS06X200L	6mm	200m	Lime	4.2kg	0.70 t
PS06X100W	6mm	100m	White	2.9kg	0.70 t
PS06X100R	6mm	100m	Red	2.9kg	0.70 t
PS06X100BU	6mm	100m	Blue	2.9kg	0.70 t
PS06X100L	6mm	100m	Lime	2.9kg	0.70 t
PS08X100W	8mm	100m	White	5.5kg	1.23 t

\*B/S—Breaking strengths quoted are based either on the Australian rope standards or in the absence of standards the manufacturers stated breaking strength. They are approximate and for comparison purposes only. **The breaking strength should never be considered as the safe working load of the rope.**