

ROPE 3 & 8 Strand

Manila Rope
 Sisal Rope
 Polypropylene Rope
 Silver (PE) Rope
 PE Mono Rope
 Polydacron Rope
 Polyester Rope
 Nylon Rope
 Square (8 Strand)
 Hardy Hemp
 Dyneema
 Cotton Rope
 Mini Coils
 Anchor Ropes

CORDS Braids & Plaits

Abseiling Rope
 Brickies Line
 Cod End Line
 Dinghy Braid
 Double Braid
 Flag Cord
 Lead Core Line
 Luff Cord/Leech Line
 Motor Starter Cord
 Polyester Cord Pltd
 Pre-stretch 8 Plt
 Sash Cord, Braided
 Shock Cord
 Ski Rope
 Spectra Cord
 Vectra Cord
 VB Cord
 Webbing

TWINES

Baler Twine
 Binder Twine
 Butchers Twine
 Garden Twine
 Jute Market Garden
 Jute Sewing Twine
 Lashing
 Plumbers Hemp
 Sailmakers Twine
 Shop Twine
 Tarred Marline
 Ticketing Twine
 Tomato Twine
 Whipping Twine

NETS/LADDERS

Rope Nets
 Tie Down Nets
 Rope Ladders

OTHER ITEMS

Clothes Line
 Barbed Wire Cutters
 Heat Cutters
 Rope Measurer

DOOR MATS

Coir Door Mats
 Wire Brush Mats
 Coir Mat Logos

POLYETHYLENE SILVER ROPE (3 Strand)

Characteristics: Polyethylene fibrillated (hairy) marine rope. Good resistance to sunlight. UV Stabilised. Knots well. Light weight. Floats, easy to handle. White in colour.

Applications: Tie Down, Camping, Swings/Kids outdoor play, Boating.



Code	Size	Length	Unit	Colour	Weight	*B/S
Spools						
SL04S250	4mm	250m	Spool	White	2.4kg	0.21 t
SL04S500	4mm	500m	Spool	White	4.8kg	0.21 t
SL06S250	6mm	250m	Spool	White	4.6kg	0.38 t
SL06S300	6mm	300m	Spool	White	5.5kg	0.38 t
SL08S125	8mm	125m	Spool	White	3.9kg	0.62 t
SL10S125	10mm	125m	Spool	White	6.2kg	0.94 t
SL12S080	12mm	80m	Spool	White	5.7kg	1.26 t
SL12S125	12mm	125m	Spool	White	8.9kg	1.26 t
SL14S080	14mm	80m	Spool	White	7.7kg	1.44 t
SL14S125	14mm	125m	Spool	White	12.1kg	1.44 t
SL16S050	16mm	50m	Spool	White	6.3kg	2.12 t
SL16S125	16mm	125m	Spool	White	15.8kg	2.12 t
Coils						
SL04C500	4mm	500m	Coil	White	4.8kg	0.21 t
SL06C250	6mm	250m	Coil	White	4.6kg	0.38 t
SL08C250	8mm	250m	Coil	White	7.9kg	0.62 t
SL10C250	10mm	250m	Coil	White	12.5kg	0.94 t
SL12C250	12mm	250m	Coil	White	17.7kg	1.26 t
SL14C250	14mm	250m	Coil	White	24.2kg	1.44 t
SL16C250	16mm	250m	Coil	White	31.7kg	2.12 t
SL18C125	18mm	125m	Coil	White	20.0kg	2.59 t
SL18C250	18mm	250m	Coil	White	40.1kg	2.59 t
SL20C125	20mm	125m	Coil	White	24.7kg	3.16 t
SL20C250	20mm	250m	Coil	White	49.5kg	3.16 t
SL22C125	22mm	125m	Coil	White	30.0kg	3.75 t
SL22C250	22mm	250m	Coil	White	60.1kg	3.75 t
SL24C125	24mm	125m	Coil	White	36.0kg	4.39 t
SL24C250	24mm	250m	Coil	White	71.3kg	4.39 t
SL28C125	28mm	125m	Coil	White	48.4kg	5.94 t
SL28C250	28mm	250m	Coil	White	96.9kg	5.94 t
SL32C125	32mm	125m	Coil	White	63.5kg	7.77 t
SL32C250	32mm	250m	Coil	White	127.0kg	7.77 t
SL36C125	36mm	125m	Coil	White	80.0kg	9.82 t
SL40C125	40mm	125m	Coil	White	98.5kg	12.13 t

*B/S—Breaking strengths quoted are based either on the Australian rope standards or in the absence of standards the manufacturers stated breaking strength. They are approximate and for comparison purposes only. **The breaking strength should never be considered as the safe working load of the rope.**